

# PK-1500

Door/Wall mount Panel Air Conditioner

## COOLING CAPACITY

## 1500W



Features	UoM	PK-1500
Cooling Capacity EN 14511 A35 A35	W	1500
Cooling Capacity EN 14511 A35 A50	W	1250
Power supply	V-Hz	230 1~ 50-60
Width	mm	400
Height	mm	950
Depth	mm	250
Rated Current max.	A	5.5
Starting Current max	A	12
Power Draw EN 14511 A35 A35	W	870
Power Draw EN 14511 A35 A50	W	1300
R134a Refrigerant	g	500
Max. refrigeration circuit Pressure	bar	28
Internal Circuit Air Flow	M3/h	600
External Circuit Air Flow	M3/h	1000
Internal temperature setting Range	C°	20-45
External Maximum Temperature	C°	50
EN60529 Ingress Protection-Internal	-	IP54
EN60529 Ingress Protection-External	-	IP34
Temperature Controller	-	Digital-Factory Set 30-35 C°
Noise Level	Db(A)	65
Weight	Kg	42
Standard Color	-	RAL 7035
Evaporator Coil Protection	-	D-Coat (Details available)
Mounting on Enclosure	-	External

### Accessories

S.S Body (S.S 201, S.S 304 )

Coating in Not Standard Color

Metal Filters

### Performance

