

PK-300

Door/Wall mount Panel Air Conditioner

COOLING CAPACITY

300W



Features	UoM	PK-300
Cooling Capacity EN 14511 A35 A35	W	300
Cooling Capacity EN 14511 A35 A50	W	200
Power supply	V-Hz	230 1~ 50-60
Width	mm	300
Height	mm	550
Depth	mm	140
Rated Current max.	A	1.6
Starting Current max.	A	3.4
Power Draw EN 14511 A35 A35	W	270
Power Draw EN 14511 A35 A50	W	310
R134a Refrigerant	g	120
Max. refrigeration circuit Pressure	bar	25
Internal Circuit Air Flow	M3/h	280
External Circuit Air Flow	M3/h	280
Internal temperature setting Range	C°	20-45
External Maximum Temperature	C°	50
EN60529 Ingress Protection-Internal	-	IP54
EN60529 Ingress Protection-External	-	IP34
Temperature Controller	-	Digital-Factory Set 30-35 C°
Noise Level	Db(A)	61
Weight	Kg	14
Standard Color	-	RAL 7035
Evaporator Coil Protection	-	D-Coat (Details available)
Mounting on Enclosure	-	External

Accessories

S.S Body (S.S 201, S.S 304)

Coating in Not Standard Color

Metal Filters

Performance

