

PT-800

Door/Wall mount Panel Air Conditioner

COOLING CAPACITY



Accessories

S.S Body (S.S 201, S.S 304)

Coating in Not Standard Color

Metal Filters

820W

Features	UoM	PT-800
Cooling Capacity EN 14511 A35 A35	W	820
Cooling Capacity EN 14511 A35 A50	W	650
Power supply	V-Hz	230 1~ 50-60
Width	mm	300
Height	mm	700
Depth	mm	250
Rated Current max.	A	2.6
Starting Current max	A	9.5
Power Draw EN 14511 A35 A35	W	410
Power Draw EN 14511 A35 A50	W	490
R134a Refrigerant	g	210
Max. refrigeration circuit Pressure	bar	28
Internal Circuit Air Flow	M3/h	330
External Circuit Air Flow	M3/h	570
Internal temperature setting Range	C°	20-45
External Maximum Temperature	C°	50
EN60529 Ingress Protection-Internal	-	IP54
EN60529 Ingress Protection-External	-	IP34
Temperature Controller	-	Digital-Factory Set 30-35 C°
Noise Level	Db(A)	65
Weight	Kg	27
Standard Color	-	RAL 7035
Evaporator Coil Protection	-	D-Coat (Details available)
Mounting on Enclosure	-	External

Performance

